









<p>Hydro-Tec 45 Garment Description:</p> <p><i>These garments are designed for specific work utility for protection and coverage from hydro blasting or similar work operations. The Hydro-Tec 45 series garments offer excellent abrasion strength and tear resistance, as well as protection from liquid penetration or incidental chemical splash.</i></p>	<p>Hydro-Tec 45 Fabric:</p> 
<p>Hydro-Tec 45 Garment Construction:</p> <p><i>All stitching, except garment hems, are to be double needle stitched. All seams in the garment, except the hems, are to be sealed on the coated side of the fabric with a clear 7/8" wide PVC tape making the garment 100% waterproof.</i></p>	<p>Hydro-Tec 45 Suggested Applications:</p> <ul style="list-style-type: none"> • Containment Tank Cleaning • Hydro Blasting • Petro Chemical Plant Maintenance • Sewer & Water Works • Sanitation & General Industrial
<p>Hydro-Tec 45 Featured Garments:</p>	
 <p style="text-align: center;">HT45AJ</p> <ul style="list-style-type: none"> • Attached Hood with Draw Cord • Neck Tab & Storm Flap Closures with Hook & Loop • Snap-Up Front & Draw Cord In Bottom Sweep • Take-Up Tabs On Sleeves with Hook & Loop 	
 <p style="text-align: center;">HT45BT</p> <ul style="list-style-type: none"> • Chest High Full-Around Coverage • Wide Leg Design • Adjustable Elastic Suspenders with Back Divider • Take-Up Tabs On Lower Legs with Hook & Loop 	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">  <p style="text-align: center;">Liquid Penetration ASTM F903</p> </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">  <p style="text-align: center;">“Limited Flame Resistance” ASTM D6413</p> </div> <div style="border: 1px solid black; padding: 5px;"> <p>Additional Features & Styles Available:</p> <ul style="list-style-type: none"> • Alternative Material = Hydro-Tec 35 </div>



Hydro-Tec – 45 Series



Hydro-Tec 45 Garment Material Information:

Fabric:	Neoprene/Nylon	Weight:	12.8 oz/sq. yd.(+/- .05)	Thickness:	.34 mm
Fabric Coating:	Neoprene	Base Fabric:	Nylon (210 Denier)		
Hydrostatic:	178 + PSI	Tear:	16.5	Tensile:	109
Limited Flame Resistance:	ASTM D6413	Liquid Penetration Resistance:	ASTM F903		
Available Colors:	Yellow, Green & Orange			Available Sizes:	Small – 6X

Hydro-Tec 45 Series Available Garment Options:

Style:	HT45AJ	Item Number (S-2X):	45010-00-1	Item Number (3X-2X):	45010-00-2
Description:	Jacket w Attached Hood, Neck Tab Closure, Storm Flap, & Take-Up Tabs				
Style:	HT45BT	Item Number (S-2X):	45010-12-1	Item Number (3X-2X):	45010-12-1
Description:	Bib Trousers w Adjustable Straps, & Take-Up Tabs				

Hydro-Tec 45 Series Garment Sizing & Measurements (Inches)

Jacket	S	M	L	XL	2X	3X	4X	5X	6X
Chest Size:	36-38	40-42	44-46	48-50	52-54	56-58	60-62	64-66	68-70
Chest:	48	51	55	59	63	67	71	74.5	78.5
Arm Length:	33.3	34.3	35.3	36	37	38	39	40	41
Jacket Length:	29.8	29.8	30	30	30.3	30.3	30.5	30.5	30.8
Bib Trousers									
Top of Bib:	10.5	11	11.5	12	12.5	13	13.5	14	14.5
Waist:	49	51.5	54	56	58	60.5	63	65	67.5
Inseam:	28.5	28.8	29	29	29.3	29.3	29.5	29.	29.8

Hydro-Tec 45 Garment Care Information

	Synthetic Wash Reduced (Medium) Use Mild Detergent No Fabric Softeners
	Do Not Iron
	Do Not Use Chlorine Bleach
	Do Not Tumble Dry – Line Dry Only
	Do Not Dry Clean



Post Office Box 1059 • Gonzales, Louisiana 70707
 Phone 800.535.8042 • Fax 225.644.3517
www.neeseind.com

“Protecting What Matters Most”