



Garment Series Description:		Garment Series Construction:	
<p>These FR Coveralls are designed for the wearer's comfort, workplace utility, and reliable protection from FR hazards. For your everyday wear needs, the NeeseWear FR Coveralls are made from certified components and a variety of FR fabrics that will keep you comfortable and protected.</p>		<p>All garment stitching is done with NOMEX® IIIA thread. All seams (excluding hems) are double needle stitched using 1/4" wide stitching lock-down safety stitching throughout with a feld seam seat and bar tacked stress points to insure garment durability and integrity.</p>	
 <div style="display: flex; justify-content: center; align-items: center; gap: 10px;">    </div> <div style="display: flex; justify-content: center; align-items: center; gap: 10px; margin-top: 10px;">   </div>		Suggested Garment Applications:	
		<ul style="list-style-type: none"> • Petrochemical Plant & Refinery Wear • Electrical & Gas Utilities • Electrical Maintenance Operations • Electrical Switching Operations • Flash Fire Hazardous Environments • Oil & Natural Gas Extraction • Drilling & Pipeline Servicing/Maintenance 	
		Garment Series Features:	
		<p>Standard Coverall Features:</p> <ul style="list-style-type: none"> • Leaf Collar • Front Storm Flap with Covered Snaps • FR Zipper Front Closure • Double Stitched Pockets: • 2 Chest, 2 Rear, 2 Hip, 1 Tool • Pleated Upper "Action Back" • Elastic Waist • Side Hip Pass Through (Both Sides) <p>Optional Up-Fit Features:</p> <ul style="list-style-type: none"> • Additional Side Leg Zippers • Additional Reflective Tape Configurations • Additional Logo Placement & Special Patches 	
Standards (Meets or Exceeds):	NFPA 2112, and NFPA 70E, 1971, 1975, 1977, & ASTM F1506 Arc Thermal Performance Tested, Garment = UL Listed		
Available Colors:	Navy Blue (NV), Gray (GY), Khaki (KH), & Royal Blue (RY)		
Additional Colors:	Orange (OR), Green (GN), & Red (RD)	Sizes:	Small – 6X
Basic Garment Fabric Option Information:			
Fabric:	Nomex® IIIA	Fabric Weight:	4.5 oz.
Fabric Content:	93% Nomex, 5% Kevlar, & 2% Antistatic Fiber		Style Number: VN4CA
Fabric Content:			APTV: 4.6 Cal/cm ² 
Fabric:	Nomex® IIIA	Fabric Weight:	6 oz.
Fabric Content:	93% Nomex, 5% Kevlar, & 2% Antistatic Fiber		Style Number: VN6CA
Fabric Content:			APTV: 5.8 Cal/cm ² 
Fabric:	Amplitude	Fabric Weight:	6 oz.
Fabric Content:	88% FR Cotton & 12% Nylon, Twill Weave		Style Number: VA6CA
Fabric Content:			APTV: 8.2 Cal/cm ² 
Fabric:	Amplitude	Fabric Weight:	7.7 oz.
Fabric Content:	88% FR Cotton & 12% Nylon, Twill Weave		Style Number: VA7CA
Fabric Content:			APTV: 9.2 Cal/cm ² 
Fabric:	Indura®	Fabric Weight:	9 oz.
Fabric Content:	100% FR Cotton Sateen Weave Fabric		Style Number: VI9CA
Fabric Content:			APTV: 11.5 Cal/cm ² 
Fabric:	Indura® Ultra-Soft®	Fabric Weight:	7 oz.
Fabric Content:	88% FR Cotton & 12% Nylon, Twill Weave		Style Number: VU7CA
Fabric Content:			APTV: 8.7 Cal/cm ² 
		Post Office Box 1059 • Gonzales, Louisiana 70707 Phone 800.535.8042 • Fax 225.644.3517 www.neeseind.com	
		"Protecting What Matters Most"	



• Individual Measurements for FR Basic Coveralls •

Coverall	S	M	L	XL	2X	3X	4X	5X	6X
Numeric	34/36	38/40	42/54	46/48	50/52	54/56	58/60	62/64	66/68
Chest:	41	44	48	52	56	60	64	68	72
Waist:	34	38	42	45	48	51	54	58	62
Trunk:	35	36	37	38	39	40	41	42	43
Trunk Long:	35.75	36.75	37.75	38.75	39.75	40.75	41.75	42.75	43.75
Trunk Short:	34.25	35.25	36.25	37.25	38.25	39.25	40.25	41.25	42.25
Inseam:	29	29.5	30	30.5	31	31.5	32	32.5	33
Inseam Long:	30.5	31	31.5	32	32.5	33	33.5	34	34.5
Sleeve:	31	32	34	36	37	38	40	41	42
Sleeve Long:	32.75	33.75	35.75	37.75	38.75	39.75	41.75	42.75	43.75
Sleeve Short:	29.25	30.25	32.25	34.25	35.25	36.25	38.25	39.25	40.25

(Measurements Have Variance of + / - 1")

• Care Instructions for Garment (NOMEX® IIIA) •

Garments of DuPont NOMEX® brand fiber can be cleaned by home or commercial laundry or by dry cleaning procedures without loss of their inherent protective features. The following suggestions will help keep your garments looking neat, attractive and safe.

- If home procedures do not remove contaminants, commercial laundering or dry cleaning is recommended.
- Launder garments of NOMEX® separate from personal non-flame resistant clothing to help avoid contamination by flammable materials.
- Pretreat greasy stains and collar/cuff lines.
- Wash garments in hot water with a heavy-duty detergent. Do not overload home laundry equipment.
- Do not use chlorine bleach or detergents containing chlorine bleach. Chlorine bleach may cause fading and reduce fabric strength. However chlorine bleach will not affect the inherent flame resistance of NOMEX® thermal technology.
- Tumble dry garments at a low setting. Use the cool-down cycle if available. Remove and hang garments as soon as tumbler stops. Do not hang in direct sun-sunlight can cause fading and reduce fabric strength.
- When using commercial laundry aids, be sure to read and carefully follow the manufacturer's instructions.

• Laundering Instructions for FR Cotton or Blend Garment •

Washing

- Do not overload washer.
- Use high water level.
- Wash at temperature necessary to clean garment. (maximum 165°F, or 74°C).
- Use recommended amount of quality detergent. (Phosphate can be used)
- Do not use chlorine bleach or hydrogen peroxide – separately or in detergents.
- Do not use softeners or starch.
- Do not use tallow soap (i.e., one containing animal fats).
- For best results, use an acid sour when industrial laundering.
- Softened water provides best results.

Drying

- Do not use extreme heat or leave in for long periods. (Maximum stack temperature 165° F, or 74° C)
- The basket temperature should not exceed 280° F, or 138° C.
- Remove garment immediately when dry or when slightly damp. Complete drying on a hanger. Overdrying will result in excessive shrinkage.
- Garments may be line dried.

Pressing

- Garments may be pressed to remove wrinkles.
- Use cotton setting.

Clean garment thoroughly. Failure to launder properly could adversely affect the flame resistance of the fabric.